

FFM2521SW

FFM's seawater high-rejection RO membrane series features higher desalination rates and stable operation, establishing it as a core component in seawater desalination systems. These membranes are suitable not only for seawater desalination but also for high-concentration brackish water treatment, power plant boiler feed water production, and various other industrial water treatment applications.

Performance Parameters

Permeate Flow:	300 gpd(1.13m ³ /d)
Salt rejection:	99.6%
Test conditions:	32000 mg/L NaCl solution
	77 F(25°C) Operating Temperature
	800 psi (5.52Mpa) Applied Pressure
	4% Permeate Recovery
	6.5-7.0 pH Range

*Single-element water outlet tolerance: ±20% (standard conditions).

Product Specifications

Dimensions-inches(mm)			
L	L1	L2	L3
21.0(533)	1.12(28.5)	0.75(19.1)	2.4(61)

Item	Specification
Configuration	Spiral Wound
Membrane Polymer	Composite Polyamide
Membrane Active Area	14ft ² (1.3m ²)



*Post-update performance may vary within specified design limits, with ±3% membrane area tolerance.

Operation Parameters

Maximum Operating Temperature:	113°F (45°C)
Maximum Operating Pressure:	1000 psi (6.9 Mpa)
Maximum Pressure Drop Per Element:	15psi (0.1 Mpa)
Maximum Pressure Drop Per Vessel:	50psi (0.35 Mpa)
pH Range, Continuous Operation:	2-11
pH Range, Short Term Cleaning (30min):	1-13
Maximum Feed Water SD(15mins):	5
Maximum Chlorine Concentration:	< 0.1mg/L

*The limitations shown here are for general use. For specialized applications or customized solutions, please contact FFM Inc. directly.